

ULC-T Line Card



The universal transmit line card, ULC-T, features DVB-S2 with Adaptive Coding and Modulation (ACM) on the outbound channel and is DVB-S2X upgradable up to 125MHz* carrier bandwidth. In conjunction with a multi-channel demodulator line card (e.g. ULC-R), the ULC-T is ideally suited for broadband applications such as Internet and VPN access to enterprise networks, along with real-time VoIP and videoconferencing on both the iDirect Evolution® and Velocity™ platforms.

Network Configuration

Network Technology	DVB-S2, DVB-S2X-ready*
Modem	One Modulator (Transmit one downstream carrier)
Modulation	QPSK, 8PSK, 16APSK, 32APSK
FEC	LDPC 1/4 - 8/9
Symbol Rate	Up to 45 Msps
Maximum IP Data Rate	182 Mbps (32APSK max)
Interoperability	Compatible with Series 15100 Universal Hub (5IF/20 Slot) Requires Evolution 3.4 / Velocity 1.1 software or above

Interfaces

SatCom Interfaces	TxIF: Type-F, 950–2000 MHz, +5/-35 dBm power
Data Interfaces	GigE LAN A: Data & Control; GigE LAN B: Data & Control. Link Aggregation. Console: RS232 over RJ-45
Timing Interface	Locked to customer supplied PPS/10 MHz through backplane
Other Features	Linear pre-distortion

Mechanical/Environmental

Redundancy	Software controlled, hot-swappable, and auto-failover
Weight	0.83 kg (1.48 lbs)
Operating Temperature	0° to +45°C (+32° to +113°F), 0–95% non condensing
Input Voltage	24V; 65W (max)
Certifications (System Level)	FCC, CE, and RoHS Compliant

* Future software release

VT iDirect, Inc.

13861 Sunrise Valley Drive
Herndon, VA 20171
Tel: +1 703.648.8000
+1 866.345.0983
www.idirect.net